



## 298.00 EUR

incl. 19% VAT, plus shipping

- High brightness !
- Audio speakers !
- Rear CAM feature !
- Auto-PowerOn !

New : LED-Backlight-Technology, with optimized color saturation enabling particular high and shining display. The scale of displayable color nuances is increased by 45% because of the new technology. Conventional LCDs are based on CCFL backlight, which can display approx. 72% of the standard color scale of NTSC (National Television Systems Committee). With LED-Backlight-Technology 104% of the NTSC-color scale can be displayed. This results in displaying in a highly realistic manner.

The new CTFHD-700 TFT-Display is the ideal display- and input-unit for your Laptop, CarPC or HTPC. With the touchscreen functionality you easily can control your PC. The briliant HDMI-display ensures a maximum readability and sharpness.

The device has integrated Stereo-speakers, a rear camera input and the dimmer button in the front will enable perfect viewing pleasure also during the night.

AC-Adapter for home usage and a car cigarette lighter adapter is included as well as the IR-remote-control unit and the extra long (2,5 meters) All-In-One connector cable.

The CTFHD-700 can be used with any PC/MAC with HDMI- and USB port.



Driver-CD included, compatible with :

- Windows 95/98/ME/NT4/2000/XP/7/8/8.1/10
- XP Tablet PC Edition
- Windows CE 2.12, 3.0, .net
- Linux RedHat,Mandrake,...
- Macintosh OS 9.x, 10.x
- DOS,..

Screen size 7" digital   Touchscreen Resistive (also available without Touchscreen or with capacitive Multi-Touschreen)   Aspect Ratio 16:9 wide TFT screen   Dot Resolution 2400x480= 1,152,000 dots   Physical Resolution 800x480   Supported Resolutions 640x480-1920x1200 (also eg. 1366x768)   Color configuration RGB stripe   Power input DC 12/24V   Power consumption max. 8W   Video system 3x Video inputs (PAL/NTSC) 1x HDMI input   Dimensions Display Case : 184x129x32 mm Display Case : 184x129x32 mm   Display Case : 184x129x32 mm Display Case : 184x129x32 mm   Display Case : 184x129x32 mm Display Case : 184x129x32 mm   Display Case : 184x129x32 mm Display Case : 184x129x32 mm   Display Case : 184x129x32 mm Display Case : 184x129x32 mm   Display Case : 184x129x32 mm Display Case : 184x129x32 mm   Display Case : 184x129x32 mm Display Case : 184x129x32 mm   Display Case : 184x129x32 mm Display Case : 184x129x32 mm   Display Case : 184x129x32 mm Display Case : 184x129x32 mm   Display Case : 184x129x32 mm Display Case : 184x129x32 mm   Display Case : 184x129x32 mm <th></th>	
Aspect Ratio 16:9 wide TFT screen   Dot Resolution 2400x480=1,152,000 dots   Physical Resolutions 640x480-1920x1200 (also eg. 1366x768)   Supported Resolutions 640x480-1920x1200 (also eg. 1366x768)   Color configuration RGB stripe   Power input DC 12/24V   Power consumption max. 8W   Video system 3x Video inputs (PAL/NTSC)   1x HDMI input Display Case : 184x129x32 mm   Display Case : 184x129x32 mm Display : 154 x 93 mm   Video input signal 1.0Vp-p, composite video   Brightness 500 cd/m²   Contrast 500:1   Vibration EC68-2-6   Operating Temperature 20° bis 70°C   Features Full function OSD control (englisch)   Built-in Stereo-speakers Suilt-in Stereo-speakers	
Dot Resolution2400x480= 1,152,000 dotsPhysical Resolution800x480Supported Resolutions640x480-1920x1200 (also eg. 1366x768)Color configurationRGB stripePower inputDC 12/24VPower consumptionmax. 8WVideo system3x Video inputs (PAL/NTSC) 1x HDMI inputDimensionsDisplay Case : 184x129x32 mm Display : 154 x 93 mmVideo input signal1.0Vp-p, composite videoBrightness500 cd/m²Contrast500:1VibrationEC68-2-6Operating Temperature20° bis 70°CFeaturesFull function OSD control (englisch)Built-in Stereo-speakers	
Physical Resolution 800x480   Supported Resolutions 640x480-1920x1200 (also eg. 1366x768)   Color configuration RGB stripe   Power input DC 12/24V   Power consumption max. 8W   Video system 3x Video inputs (PAL/NTSC)   1x HDMI input Display Case : 184x129x32 mm   Display Case : 184x129x32 mm Display : 154 x 93 mm   Video input signal 1.0Vp-p, composite video   Brightness 500 cd/m²   Contrast 500:1   Vibration EC68-2-6   Operating Temperature 20° bis 70°C   Features Full function OSD control (englisch)   Built-in Stereo-speakers Built-in Stereo-speakers	
Supported Resolutions \$40x480-1920x1200 (also eg. 1366x768)   Color configuration RGB stripe   Power input DC 12/24V   Power consumption max. 8W   Video system 3x Video inputs (PAL/NTSC)   1x HDMI input Display Case : 184x129x32 mm   Dimensions Display Case : 184x129x32 mm   Display : 154 x 93 mm Display : 154 x 93 mm   Video input signal 1.0Vp-p, composite video   Brightness 500 cd/m²   Contrast 500:1   Vibration IEC68-2-6   Operating Temperature 20° bis 70°C   Features Full function OSD control (englisch)   Built-in Stereo-speakers Sult-in Stereo-speakers	
Color configuration RGB stripe   Power input DC 12/24V   Power consumption max. 8W   Video system 3x Video inputs (PAL/NTSC)   1x HDMI input 1x HDMI input   Dimensions Display Case : 184x129x32 mm   Display : 154 x 93 mm Display : 154 x 93 mm   Video input signal 1.0Vp-p, composite video   Brightness 500 cd/m²   Contrast 500:1   Vibration IEC68-2-6   Operating Temperature 20° bis 70°C   Features Full function OSD control (englisch)   Built-in Stereo-speakers Suilt-in Stereo-speakers	
Power inputDC 12/24VPower consumptionmax. 8WVideo system3x Video inputs (PAL/NTSC) 1x HDMI inputDimensionsDisplay Case : 184x129x32 mm Display Case : 184x129x32 mmDimensionsDisplay Case : 184x129x32 mm Display : 154 x 93 mmVideo input signal1.0Vp-p, composite videoBrightness500 cd/m²Contrast500:1VibrationIEC68-2-6Operating Temperature20° bis 70°CFeaturesFull function OSD control (englisch)Built-in Stereo-speakers	
Power consumptionmax. 8WVideo system3x Video inputs (PAL/NTSC) 1x HDMI inputDimensionsDisplay Case : 184x129x32 mm Display : 154 x 93 mmVideo input signal1.0Vp-p, composite videoBrightness500 cd/m²Contrast500:1VibrationIEC68-2-6Operating Temperature20° bis 70°CFeaturesFull function OSD control (englisch)Built-in Stereo-speakers	
Video system3x Video inputs (PAL/NTSC) 1x HDMI inputDimensionsDisplay Case : 184x129x32 mm Display : 154 x 93 mmVideo input signal1.0Vp-p, composite videoBrightness500 cd/m²Contrast500:1VibrationIEC68-2-6Operating Temperature Features-20° bis 70°CFeaturesFull function OSD control (englisch)Built-in Stereo-speakers	
Video system1x HDMI inputDimensionsDisplay Case : 184x129x32 mmDisplay : 154 x 93 mmVideo input signal1.0Vp-p, composite videoBrightness500 cd/m²Contrast500:1VibrationIEC68-2-6Operating Temperature20° bis 70°CFeaturesFull function OSD control (englisch)Built-in Stereo-speakers	
1x HDMI input   Display Case : 184x129x32 mm   Display : 154 x 93 mm   Video input signal   1.0Vp-p, composite video   Brightness   500 cd/m²   Contrast   500:1   Vibration   IEC68-2-6   Operating Temperature   20° bis 70°C   Features   Full function OSD control (englisch)   Built-in Stereo-speakers	
Dimensions Display : 154 x 93 mm   Video input signal 1.0Vp-p, composite video   Brightness 500 cd/m²   Contrast 500:1   Vibration IEC68-2-6   Operating Temperature -20° bis 70°C   Features Full function OSD control (englisch)   Built-in Stereo-speakers Built-in Stereo-speakers	
Display : 154 x 93 mm   Video input signal 1.0Vp-p, composite video   Brightness 500 cd/m²   Contrast 500:1   Vibration IEC68-2-6   Operating Temperature 20° bis 70°C   Features Full function OSD control (englisch)   Built-in Stereo-speakers Built-in Stereo-speakers	
Brightness 500 cd/m²   Contrast 500:1   Vibration IEC68-2-6   Operating Temperature 20° bis 70°C   Features Full function OSD control (englisch)   Built-in Stereo-speakers	
Contrast 500:1   Vibration IEC68-2-6   Operating Temperature -20° bis 70°C   Features Full function OSD control (englisch)   Built-in Stereo-speakers	
Vibration IEC68-2-6   Operating Temperature -20° bis 70°C   Features Full function OSD control (englisch)   Built-in Stereo-speakers	
Operating Temperature -20° bis 70°C Features Full function OSD control (englisch) Built-in Stereo-speakers	
Features   Full function OSD control (englisch)     Built-in Stereo-speakers   Built-in Stereo-speakers	
Built-in Stereo-speakers	
Auto Power On/Off	
Auto-Dimmer	
Earphone-Output (rear side)	
Automatic switching to rear camera (by signal detection on AV3)	
What is included ? - 7" HDMI Touchscreen TFT with Video/Audio-support	
- Infrared Remote Control	
- Car dash mounting bracket	
- Touchscreen pencil	
- HDMI/Video/Audio/Touchscreen-cable (all-in-one !) 2,5 meters length	
- Power Adapter f. EU 230V	
- Cigarette Lighter Adapter	
- Touchscreen Driver-CD	
- Manual	



Displays with <u>True-800x480-Support</u> achieve a pixel accurate view at 800x480@70Hz