



129.00 EUR

incl. 19% VAT, plus [shipping](#)

- Displaylink !
- 800x480 !
- Touchscreen !
- VESA-75 !



Difference to UM-720S : VESA (75mm) compatible mounting option on display rear side. You can mount the display on any VESA compatible mounting unit. Please take notice of the fact that there is no mounting unit included in scope of supply !

This TFT monitor is connected to a Windows PC USB connector. The display is working as an additional display which can be added to the main display area on the left, right, upper or lower. Alternatively it can mirror the primary screen. The display can be swiveled in steps of 90°.

In addition, the UM-720F model comes with touchscreen.

For this display we offer 3 different mounting adapters :

- [Headrest-mounting adapter](#)
- [Suction mounting](#)
- [VESA-75 adapter plate](#)

Specifications :

Model	MIMO UM-720F (7")
LCD Panel Size	17.78 cm
Display Size	152.4mm (H) x 91.4mm (V)
Pixel Pitch	0.1905mm (H) x 0.1905mm (V)
Number of Colors	16.7M
Contrast	400:1
Brightness	350 cd/m ²
Input Power	USB (DC 5V)
Screen resolution	WVGA (800x480)
Power consumption	2W~4.5W
Dimensions	138mm (H) x 182mm (L) x 2.4mm (W)
Weight	~0,6 kg

System requirements:

- CPU : 1.2Ghz+
- RAM : 512MB RAM+
- USB : min. 1x USB 2.0
- HDD : 30MB
- OS : Windows 2000 SP4, Windows XP SP2 (32bit), Windows Vista & 7 (32bit/64bit)

Notes :

- 3D applicationes (eg. 3D games) can not be displayed.

- How many displays can be connected to a PC at the same time ?

1-2 displays : 1.2Ghz CPU, 512MB RAM

3-5 displays : 1.8Ghz CPU, 1GB RAM

6++ displays : 1.6Ghz Dual-Core CPU, 1GB RAM

- MAC OS Support ?

Display, webcam, etc. : Yes

Touchscreen (MAC OS) : Right now only available with non-free 3-rd party driver.

Touchscreen-Driver for Windows is free and included with the shipment !