



198.00 EUR

incl. 19% VAT, plus [shipping](#)

- Pentium-M/Celeron-M
- Ideal for M2-ATX
- Mini-PCI slots

Support:  [Manual \[EN\]](#)

- for Pentium-M and Celeron-M CPUs, 533/400FSB up to 2.26 GHz
- 1x 184-pin DIMM socket (DDR 200/266/333, up to 1GB)
- 1x 44-pin Standard-IDE Port
- 1x 40-pin Slim-IDE Port (for 2.5" HDD)
- 1x PCI
- 2x Mini-PCI
- 1x Gigabit LAN
- Graphics adapter onboard (Intel Extreme Technology)
- Sound onboard (Realtek ALC655 5.1 AC97)
- Standard ATX power connector
- TV-Out

Scope of supply :

- LV675D mainboard
- Slim CPU Alu cooler
- DVI output cable kit
- IDE-cable (40 pin)
- IDE-cable (44 pin)
- Floppy-cable (26 pin)
- COM-port-cable-kit

Manual online : [Here](#)Graphics driver for 800x480 resolution : [Here](#)**Spezifikationen :****Form Factor**

Mini-ITX form factor at 170 x 170 mm

CPU

Micro-FCPGA 478 Mobile Intel Pentium M / Celeron M CPU up to 2.26 GHz @ 400/533 MHz FSB

Memory

One 184-pin DIMM socket Support up to 1 GBytes DDR 200/266/333 SDRAM

Chipset	Intel high performance chipset
Watchdog Timer	Generates a system reset with internal timer for 1 to 255 sec.
Power Management	ACPI 2.0 compliant, supports power saving mode .
Real Time Clock	Intel ICH4 built-in RTC with onboard lithium battery
PCI Enhanced IDE	40-pin UltraATA/100 bus master IDE channels And one onboard 44-pin IDE connector
VGA Interface	Built-in Intel Extreme Graphics Video Memory up to 64 MB shared with system
LVDS /DVI Interface	External DB15 female connector on rear I/O panel
TV-out Interface	Optional Dual channel 18/24-bit LVDS or DVI interface
LAN Interface	S-video & Composite TV-out
Audio Interface	Intel 82541PI Giga Mbps Ethernet interface
Hi-Speed USB 2.0	Onboard ACL655 AC97 3D audio codec 5.1 channel, line-in, line-out, Mic-in, CD-in and S/P DIF interface
Multi-I/O Port	Intel ICH4 chipset built-in Hi-Speed USB 2.0 interface with 480 Mbps of data transfer rate and bootable setting in BIOS
Solid State Disk	1 x RS232 & 1 x RS232/422/485, 1 x parallel, 4 x USB 2.0, 1 x IrDA, 1 x FDD, 8-bit GPIO, 1 x PS/2 keyboard and mouse port.
Expansive Slot	IDE support DiskOn Module with +5V power supply
Environment	One 32-bit PCI slot supports 2 bus master PCI via riser card, and 2 x Mini-PCI
	Power Requirement: Standard 20/24-pin ATX power supply Dimension (W x L): 170mm x 170mm with standard Mini-ITX form factor Operation Temperature: 0 ~ 60oC (32 ~ 140oF)