




198.95 EUR
incl. 19% VAT, plus [shipping](#)

Support: [Specifications](#) | [Troubleshooting](#) | [Manual](#)

This board is produced by MITAC, the OEM producer of Intel DN2800MT. This board is based on Intel DN2800MT, but is equipped with the modern Intel BayTrail platform.

- Successor model of Intel D945GSEJT and DN2800MT mainboard
- Quad-core Intel Celeron J1900
- Slim form factor; <20mm z-height
- Meets channel All-In-One specification
- ExpressCard/34 adapter option (mobile ecosystem compatibility) via PCIe mini Card
- Supports new Mobile SATA (SSD) card via full-length PCIe Mini Card
- Supports Z-U130 flash drive
- Wide-range (10-19V) input voltage tolerance
- TPM stuffing option

Name	Mitac PD10BI
Form Factor	Mini-ITX Mainboard
CPU	Intel® Celeron™ J1900 (4x 2.42GHz) 2MB Cache, VT-x/Intel64-compatible
Graphics	VGA + HDMI + LVDS + eDP
Memory	2x SO-DDR3L [Low Voltage, 1.35V] 1066/1333, 8GB max, Dual channel
LAN	1x Realtek RTL8111G-CG 10/100/1000 MBit
Connectors (rear)	- 2x USB 3.0, 2x USB2.0 - 1x LAN RJ-45 - 2x Audio - 1x HDMI - 1x VGA - 1x DC-In (10-19V)
Audio	2+2 Channel HD Audio

Connectors (internal)	- 2x SATA-II (3GB/s) - 5x USB 2.0 - 1x PCIe - 2x Mini-PCle - Front Audio - SPDIF - 1x LPT - 2x RS232 - LVDS (Dual 24bit) - eDP (4-lane 24bit) - Z-U130 Flash Drive support - TPM stuffing option - Mobile SATA (SSD) support via Mini-PCle - ExpressCard/34 support via Mini-PCle
Included	- Mitac PD10BI Mainboard (with 4x 2.42Ghz Celeron CPU) - I/O ATX rear plate (Thin + Standard) - 1x SATA cable