



89.00 EUR  
 incl. 19% VAT, plus [shipping](#)

- NTEL® H61 Express Chipset
  - Support 2nd generation Intel Core processor(i3/i5/i7) family
  - Multi-monitor support with Windows \* 7
  - Support PCI-Express 2.0
  - Support USB 3.0
  - Support Dual Channel DDR3 1333/1066
  - Integrated HD Audio CODEC with 6.0 CH
  - Support Gigabit LAN
  - 3+1+1 Phase CPU Power Support
  - Ready for Windows® 7™
  - ITX Form Factor(170mm X 170mm)
- **CPU**
    - **INTEL® LGA1155 Socket**
    - Support 2nd generation Intel Core processor(i3/i5/i7) family
    - Support Intel® Pentium® processor, and Intel® Celeron® processor.
    - Support Intel® Turbo Boost Technology 2.0
    - 3+1+1 Phase CPU Power Support
  - **Chipset**
    - INTEL® H61 Express Chipset
    - Dual Channel DDR3 memory technology
  - **Memory**
    - 2 x DDR3 DIMM slots
    - Support DDR3 1333/1066 un-buffered memory
    - Max. capacity of system memory up to: 8GB
  - **Expansion Slots**
    - 1x PCI Express 2.0 x16(By 16) slot
  - **Storage**
    - **Embedded INTEL H61 Chipset:**
    - 4 x Serial ATA2 3Gb/s connectors
    - VIA VT1705 Audio CODEC
  - **Audio**
    - 5.1 CH HD Audio with Content Protection
    - RTL8111E Chip
  - **Ethernet LAN**
    - PCI-Ex1 Gigabit LAN 10/100/1000 Mb/s
    - Support PXE
    - **INTEL H61 Chipset:**
  - **USB**
    - 6 x USB 2.0 ports (4 distribute in back panel, 2 distribute in mid-board)
    - 2 x USB 3.0 ports by ASMedia ASM1042 (2 distribute in back panel)

- **Back Panel I / O**
  - 4 x USB 2.0/1.1 ports
  - 2 x USB 3.0 ports
  - 1 x PS/2 Keyboard / Mouse
  - 1 x VGA Port
  - 1 x DVI-D Port
  - 1 x HDMI Port
  - 1 x RJ-45 Port
  - 3 x Audio jacks (Line In/Line Out/Microphone)
  - 1 x USB 2.0/1.1 header for 2 USB 2.0/1.1 ports
  - CPU / Chassis Fan connectors
- **Internal I / O**
  - 1 x 4-pin ATX 12V Power connector
  - 1 x 24-pin ATX Power connector
  - 1 x HDMI\_SPDIF header
  - 1 x Front panel audio header
- **BIOS**
  - 32 MB DIP Flash ROM
- **Form Factor**
  - ITX form Factor:170x170 mm