



164.00 EUR  
 incl. 19% VAT, plus [shipping](#)

- Intel® Celeron™ J1900 (2.0 GHz) quad-core processor
- Support DirectX 11 3D Graphics Acceleration
- Support DDR3L 1333
- Integrated HD Audio CODEC
- Support PCI Express Gigabit LAN
- Support 1\*USB3.0 Port
- Support 24-bit Dual channel LVDS
- Onboard 1\*MiniPCI-E connector
- Onboard 1 \*M- SATA connector
- 2 Phase CPU Power Support
- Support Thunder Protection Function
- [Thin mini ITX](#) Form Factor(170mm X170mm)

<b>CPU-Chipset</b>	INTEL® Celeron™ J1900 (2.0 GHz) quad-core processor • 2 Phase CPU Power Support
<b>I.O Chipset</b>	• Fintek F71808EC
<b>Memory</b>	• 2*SO-DIMM slot • Support DDR3L 1333 • Max. capacity of system memory up to 16GB

<b>Expansion Slots</b>	<ul style="list-style-type: none"> <li>1 * MiniPCI-E connector</li> </ul>
<b>Storage</b>	<ul style="list-style-type: none"> <li>1* Serial ATA2 3Gb/s connector(CO-LAY M-SATA)</li> <li>1 * <a href="#">M-SATA Connector</a></li> </ul>
<b>Audio</b>	<ul style="list-style-type: none"> <li>ALC887 Audio CODEC</li> <li>HD Audio CODEC</li> </ul>
<b>Ethernet LAN</b>	<ul style="list-style-type: none"> <li>Realtek® RTL8111G Chip</li> <li>PCI Express Gigabit LAN</li> </ul>
<b>LVDS</b>	<ul style="list-style-type: none"> <li>Onboard 24-bit Dual channel</li> </ul>
<b>USB</b>	<ul style="list-style-type: none"> <li>1* USB3.0 (EXT)</li> <li>2* USB 2.0/1.1(2 distribute in back panel)</li> </ul>
<b>Special Features</b>	<ul style="list-style-type: none"> <li>Support CPU Smart Fan</li> <li>Support Watch dog Technology</li> <li>Support GPIO Technology</li> <li>Support Amplifier function(3W)</li> <li>Thunder Protection Function</li> <li>All Solid Capacitor design for CPU</li> </ul>
<b>Back Panel I / O</b>	<ul style="list-style-type: none"> <li>1* PS/2 port</li> <li>2* USB 2.0/1.1 ports</li> <li>1* USB 3.0 port</li> <li>1* RJ-45 port</li> <li>1* DVI port</li> <li>1* VGA port</li> <li>1* 3-JACK</li> </ul>
<b>Internal I / O</b>	<ul style="list-style-type: none"> <li>2*CPU / Chassis Fan connectors</li> <li>1*COM header</li> <li>1 *24-pin ATX Power connector</li> <li>1 *24-bit Dual Channel LVDS header</li> <li>1 *GPIO header</li> <li>1 *Mini PCI-e connector</li> <li>1 * M-SATA Connector</li> <li>1* SATA Connector</li> <li>1 * Audio header</li> <li>1 * Front panel header</li> </ul>
<b>BIOS</b>	<ul style="list-style-type: none"> <li>AMI 64MB DIP Flash ROM</li> </ul>
<b>Form Factor</b>	<ul style="list-style-type: none"> <li>Thin mini ITX Form Factor(170mm X 170mm)</li> </ul>