

409.00 EUR

incl. 19% VAT, plus [shipping](#)

- JNF532-2930 (3.5 " SBC)
- INTEL® Bay Trail-M N2930 SoC Processor (1.83GHz)
- 1 * SO-DDR-3 Low Voltage (Max 8GB)
- 1 * 2.5" SATA Device (Max Height 9.5 mm)
- 1 * m-SATA SSD Device (Mini PCI-E)
- Application : Gaming,Medical,POS/KIOSK,Industrial Automation, Transportation,Telecom,Networking,I.O.T,AIO

• Dimension (W*H*D)	• 185 * 48 * 142 mm
• Construction	• Aluminum housing
• Colors	• Black
• MB model	• JNF532-2930 (3.5 " SBC)
• CPU	• INTEL® Bay Trail-M N2930 SoC Processor (1.83GHz)
• BIOS	• AMI UEFI
• Memory	• 1 * SO-DIMM slot (Max 8GB)
• Storage Space	• 1 * 2.5" SATA Device (Max Height 9.5 mm) • 1 * m-SATA SSD Device (Mini PCI-E)
• Display Interface	• 1 * DVI-D • 1 * VGA (Internal pin header)
• Network	• 2 * RJ45 (Giga Lan) • WiFi (optional / JBC375F532W-2930-B)
• Audio	• 1 * Line out • 1 * Mic in
• Front I/O Port	• 2 * USB 2.0 • 4 * COM (2x factory installation, 2x included in accessories)
• Rear I/O Port	• 3 * USB 2.0 • 1 * USB 3.0 • 2 * RJ45 • 1 * DVI-D • 1 * VGA
• Expansion Interface	• Mini PCI-E # 1 : Half-size (for mini PCIE WIFI module) • Mini PCI-E # 2 : Full-size (for M-SATA SSD)

• Power Source	• DC 9~24V Jack input • Adapter : AC_90~240V / DC_12V_5A / 60W
• Certification	• EMC : CE , FCC • Safety : RoHS , ErP
• Environment	• Operating Temperature : 0 ~ 40■ • Storage Temperature : -10 ~ 60■ • Vibration During Operation : N/A • Shock During Operation : N/A
• Mounting	• Wall mounting Kits
• Packing	• Net Weight■1.4KG • Gross Weight■2.7KG • Color Box Dimension■250(W) x 118 (D) x 295 (H) mm