



39.00 EUR incl. 19% VAT, plus shipping

5-Port Fast Ethernet Switch with 4-Port PoE provides the seamless network connection. It integrates 10/100Mbps Fast Ethernet network capabilities.

5 Auto-Negotiation RJ45 ports (port-1 to port-4) of the switch support Power over Ethernet (PoE) function. These PoE ports can automatically detect and supply power with those IEEE 802.3af compliant Powered Devices (PDs). In this situation, the electrical power is transmitted along with data in one single cable allowing you to expand your network where there are no power lines or outlets, where you wish to fix devices such as APs, IP Cameras or IP Phones, etc.

Easy To Use

Easy to install and use. It requires no configuration and installation. With desktop design, outstanding performance and quality, the 5-Port Desktop Switch with 4-Port PoE is a great selection for expanding your home or office network.

Key Features:

- * Supports PoE power up to 15.4W for each PoE port
- * Supports PoE power up to 60W for all PoE ports
- * Supports PoE IEEE 802.3af compliant PDs
- * Supports IEEE 802.3x flow control for Full-duplex Mode and backpressure for Half-duplex Mode
- * 4 ports with poe, 1 port 10/100 RJ45
- * SmartLink intelligent power management
- * One key Standard Switch/VLAN-Isolation(MTU VLAN)
- * External power adapter (65W[52V/1.25A])

| Interface | 5x 10/100Mbps RJ45 Ports |
|-----------------------|---|
| Network Media | 10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) |
| | EIA/TIA-568 100 Ω STP (maximum 100m) |
| | 100BASE-TX: UTP category 5, 5e cable (maximum 100m) |
| | EIA/TIA-568 100 Ω STP (maximum 100m) |
| Fan Quantity | Fanless |
| External Power Supply | External Power Adapter(Output: 48VDC /1.25A) |



PoE Ports (RJ45)

Backbound Bandwidth Mac Address Table Dimensions (W x D x H) Transmission Method

Advanced Functions

Certification Package Contents

Environment

POE Fast Ethernet Switch (4x POE IEEE802.3af/at, 1x LAN, VLAN, 65W) [http://www.minipc.de/catalog/il/2259]

> Standard: 802.3 af/at compliant PoE Ports: Port1- Port 4 Power Supply: 65W 1Gbps 2K 94mm(L) * 71mm(W) *26mm(H) Store-And-Forward Compatible With IEEE 802.3af Compliant PDs Priority Function EEE802.3x Flow Control full-duplex and Backpressure half-duplex IEEE802.3az EEE CE, FCC, RoHS Switch, Power Adapter Operating Temperature: -10°C~45°C Storage Temperature: -20°C~70°C Operating Humidity: 10% ~ 90% non-condensing Storage Humidity: 5%~95% non-condensing