

Jetway HPC238SC-FP1900B Panel-PC (23.8" 1920x1080 PCAP Touchscreen, Intel N2807, 2GB RAM) [IP65/NEMA4 Front] [http://www.minipc.de/catalog/il/2356]



1459.00 EUR	
incl. 19% VAT	. plus shippina

- 23.8" 250 nits high brightness TFT LCD with LED backlight
- 10-points Multi Capacitive Touch
- · Cable less, Streamlined enclosure for highly efficient heat dissipation Enclosed in robust aluminum casings
- · Edge-to-edge narrow bezel design and Fanless cooling system
- Design for easy Wall mount, Panel Mount, VESA Mount installation
- A true Flat, easy-to-clean front surface with edge-to-edge design
- Lockable USB device bracket supported
- Front bezel meets IP65-rated protection
- 9-28V DC-input Support, with EOS, OVP design

Jetway HPC238SC-FP1900B Flat-Panel Fanless Panel PC provides outstanding outlook with industrial-grade quality for comprehensive industrial markets, such as retails, wholesales, hospitality, hospital or meeting room registration, logistics, self-service kiosk, residential automation and digital signage.

Jetway HPC238SC-FP1900B Flat-Panel Fanless Panel PC is designed with 10-points Multi capacitive type touch screen. High brightness TFT LCD panel with LED backlight are equipped with this model. Cable-free design is easy for the HDD and memory installation. Streamlined enclosure with narrow bezel design.

Jetway HPC238SC-FP1900B Flat-Panel Fanless Panel PC is designed with a true flat, easy-to-clean front surface with edge-to-edge design. It is designed mounting clips for easy Wall mount, Panel Mount, VESA Mount installation.

Front bezel meets IP65-rated & NEMA 4 protection. Welcome to use Jetway Flat-Panel Panel PC.

Display	
Front Bezel	<ul> <li>IP65, NEMA 4 rugged protection, metal front bezel</li> </ul>
Display Type	- 23.8" With LED Backlight
Brightness (cd/m²)	– 250 nits
Display Color	– 16.7M
Resolution	– 1920 x1080 @ 60Hz
Viewing Angle (H/V)	– 160°/160°
Pixel Pitch	– 0.2745 x 0.2745 mm



[http://www.minipc.de/catalog/il/2356]

Aspect Ratio	- 16:9	
Contrast Ratio	- 1000:1	
Response Time	– 25 ms	
Touch Screen		
Туре	- projected capacitive type	
Active Range	– 528.04 x 297.46mm ±0.3mm	
Transparency		
Surface Hardness		
Operating Force		
Operating Temperature	– 15 ~+ 65°C	
CASE		
Panel Material	– Aluminum	
Case Material	– Iron	
Color	– Silver + white	
Coating Requirement	- Spray Paint	
Main System		
CPU	– Intel® Bay Trail-D J1900 2.0GHz/QC	
RAM	– 4G 1333MHz DDR3L SAMSUNG DRAM	
BIOS	– 64MB SPI Flash ROM	
Storage	– 1* 2.5" SATA bay	
	– 1* M.2 connector (2242/2260/2280)	
Watchdog Timer	- 256 levels, 0~255 sec.	
OS Support	– Windows 7 / 8.1 / 10 / Linux (Option)	
I/O Connector		
	– 2* USB3.0	
	- 4* USB2.0 - 2* RS232/422/485	
	- 2 KS252/422/405 - 2* RS232	
I/O Ports and Switches	– 1* CRT	
	– 1* 8bit GPIO	
	– 2* LAN (Intel® I211AT Gigabit LAN)	
	<ul> <li>– 1* Locking Jack 9~28V DC input</li> </ul>	
	– 1* Power button	
Expansion Interface		
Expansion	– 1 * PCI-E mini card for WIFI or 3G/4G	
Power		
Power Input	- Supports 9-28V DC Power in with over current protection fuse	
i over input	<ul> <li>Provides 100~240V AC-DC 12V, 60W power adapter</li> </ul>	
Power Consumption	– 42.5W	
Dimension		
Case Dimensions	- 566.04*347.46*74.0mm	
Certifications		
Certifications	- CE, FCC, IP65(Front)	
Environment		
	- Operating Temperature: 0 ~ 60° C (with W.T. DRAM/HDD in airflow condition)	
Temperature	– Storage Temperature: -20 ~ 85° C	
Shock	Operating: 15G∎11ms duration	



## Jetway HPC238SC-FP1900B Panel-PC (23.8" 1920x1080 PCAP Touchscreen, Intel N2807, 2GB RAM) [IP65/NEMA4 Front]

[http://www.minipc.de/catalog/il/2356]

Vibration	– Operating: 5~500Hz/1 Grms
Warranty	
Warranty	<ul> <li>2 Years Limited Warranty(Panel and Touch is only Warranty 1 Year)</li> </ul>