999.00 EUR
incl. 19% VAT, plus shipping

- JBC382F632W-7200-B

- Intel® Skylake-U(i5-6200U /i5-6300U), TDP: 15W
- 2 * SO-DIMM DDR4 Slot up to 32GB
- Support 1 * 2.5” SATA Device
- Support 1 * m-SATA SSD Device (Mini PCIe)
- Support DP / HDMI
- 1 * Half size Mini PCIe, 1 * Full size Mini PCIe (shared with mSATA)
- 4 * USB 2.0, 4 * USB 3.0
- 2 * Intel Gigabit LAN
- Lockable 12V DC-in Jack

| | |
|---|---|
| • Dimension (W*H*D) | • 185 * 142 * 60 mm |
| • Construction | • Aluminum housing |
| • Colors | • Black |
| • MB model | • JBC382F632-6200U-B (i5-6200U)<br>• JBC382F632-6300U-B (i5-6300U) |
| • CPU & CHIP | • INTEL® Skylake-U(i5-6200U /i5-6300U), TDP: 15W |
| • BIOS | • AMI 128Mb Flash ROM |
| • Memory | • 2 * SO-DIMM DDR4 Slot (Max. 32GB) |
| • Storage Space | • 1 * 2.5” SATA Device<br>• 1 * m-SATA SSD Device (Mini PCIe) |
| • Front I/O Port | • 2 * USB 2.0<br>• 2 * COM<br>• 1 * MIC , 1 * Line out |

| | |
|---|---|
| • Rear I/O Port | • 2 * USB 2.0 , 4 * USB 3.0<br>• 1 * DP (max resolution:4096 x 2304@60Hz)<br>• 1 * HDMI (max resolution:4096 x 2160@24Hz)<br>• 2 * RJ45 (Intel Gigabit LAN)<br>• 1 * Line out<br>• WiFi (optional / JBC382F632W-6X00U-B) |
| • Expansion Interface | • Mini PCIe # 1 : Half-size (for mini PCIe module)<br>• Mini PCIe # 2 : Full-size (shared with mSATA) |
| • Power Source | • Lockable 12V DC-in Jack<br>• Adapter : AC_90~240V / DC_12V_5A / 60W |
| • Certification | • EMC : CE , FCC<br>• Safety : RoHS , ErP |
| • Environment | • Operating Temperature : 0 ~ 50°C<br>• Storage Temperature : -20 ~ 70°C |
| • Mounting | • Wall mounting Kits |
| • Packing | • Net Weight■2.2KG<br>• Gross Weight■3.5KG<br>• Color Box Dimension■250(W) x 118 (D) x 295 (H) mm |