

324.95 EUR
 incl. 19% VAT, plus [shipping](#)



- Arduino Mega !
- 14x Digital Input !
- 10x Relay Output !
- microSD Card Support !

Support: [Datasheet](#) | [Brochure](#) | [Quick Start](#)

NORVI Arita is a higher capacity version of NORVI Series. Selection five standard models available with a choice two powerful micro-processors. Arita is designed to yield the every bit of performance in the micro-controller without compromising its reliability. It is compatible with almost every industrial input and output type. Connectivity is the factor which makes it suite today's world, for a connected world, we have included all the industrially accepted communication methods in it. Arita is used everywhere, it has many characters, it can be a motion controller handling heavy positioning tasks or a data logging server.

- 14x Sink/Source Digital Inputs
- 10x 2A Relay Output
- 2x Open collector Transistor
- 1x RS-485
- Build-in 0.96" OLED Display
- 2x 0-10V Analog Input
- 2x 4-20mA Analog Input
- 1x microSD Card Slot
- 1x W5500 Ethernet Connectivity

| | |
|----------------------|-------------------|
| Main | |
| Range of product | NORVI ARITA |
| Product type | Programmable node |
| Rated supply voltage | 24V DC |

| | |
|---------------------------------------|---|
| Discrete input number | 14 discrete input , interrupts configurable on each input |
| Discrete output type | Relay and Transistor |
| Discrete output number | 10 Relay outputs, 2 Transistor outputs |
| Analog input number | 3 |
| Discrete output voltage | 24V DC for transistor output |
| Discrete output current | 0.5A with I0.0... I0.1 Transistor 2 A with R0....R4 and Q0....Q4 Relay outputs |
| Complementary | |
| Discrete IO number | 26 |
| Number of Expansions | 4 |
| Supply voltage limits | 20.4 28.8V |
| Inrush current | <= 50A |
| Power consumption in W | 32.6 40.4 with all outputs ON |
| Discrete logic Input | Sink or source |
| Discrete input Voltage | 24V DC |
| Voltage TypeVoltage state 1 | > = 15V for Input |
| Voltage TypeVoltage state 0 | < = 5V for input |
| Discrete Input Current | 5mA for Input |
| Input impedance | 4.7k Ohm for Input |
| Battery Type (Model 8 Only) | Lithium non rechargeable - 2 years Backup at 25°C |
| Local signalling | 1 LED green for PWR 1 LED green for RUN 14 LED green for I0.....I14 10 LED green for Q0.....Q4 and R0.....R4 2 LED green for T0....T1 |
| Electrical connection | Removable screw terminal block for inputs and outputs (pitch 5.08 mm) |
| Mounting support | Top hat type TH35-15 rail conforming to IEC 60715 Top hat type TH35-7.5 rail conforming to IEC 60715 Plate or panel with fixing kit |
| Height | 86.60 mm |
| Depth | 56.60 mm |
| Width | 122.10 mm |
| Weight | 0.43 kg |
| Environment | |
| Relative humidity | 10....95% without condensation in operation |
| IP degree of protection | IP20 |
| Operating altitude | 0...2000m |
| Storage altitude | 0...3000m |
| Shock resistance | 15 gn for 11 ms |
| Resistance to electrostatic discharge | 4kV on contact, 8kV on air |
| Resistance to electro magnetic fields | 10 V/m (80 MHz 1 GHz) 3 V/m (1.4 MHz 2 GHz) 1 V/m (2 MHz 3 GHz) |
| Immunity to microbreaks | 10 ms |