



309.00 EUR
 incl. 19% VAT, plus [shipping](#)

- H610 !
- 2x COM !
- Micro-ATX !
- 3x LAN / 3x Display !



- 1. Intel® 12/13th LGA1700 Socket Processor (Max.125W TDP)
- Intel® Alder Lake-S H610E / H610 Chip
- 2* DDR4 3200MHz UDIMM up to 64GB
- 1* VGA, 1* HDMI, 1* DP
- 2* 2.5GbE, 1* GbE
- 10 or 6* COM, 3* USB3.2 (Gen.1), 7* USB2.0, 1* USB2.0 Type-A (Vertical)
- 1* M.2 M-key, 2242/2280 (PCI-Ex4), 1* M.2 M-key, 2242/2280 (SATA), 1* M.2 B-key, 3042/3052, 1* M.2 E-key, 2230, 4* SATAIII
- 1* PCI-Ex16 (Gen.4), 1* PCI-Ex4 (Gen.3), 2* PCI
- Onboard TPM2.0 (Option)
- ATX Power

Model	– LM26-H6100 (10* COM) – LM26-H6102 (10* COM, TPM2.0) – LM26-H6100-6C (6* COM) – LM26-H6102-6C (6* COM, TPM2.0)	
Form Factor	– Micro ATX (244 * 244mm)	
Processor System	– Intel® 12/13th LGA1700 Socket Core i9/i7/i5/i3/Pentium/Celeron Processor (Max. 125W TDP) – Intel® Alder lake-S H610 or H610E chipset – AMI Flash ROM BIOS	
Memory	– 2* DDR4 3200MHz Dual Channel UDIMM up to 64GB	

Storage	<ul style="list-style-type: none"> - 4* SATAIII (6 Gb/s, SATA4 Co-lay M.2 M key-M2) - 1* M.2 M-key (2242/2280 PCI-Ex4 Gen.3 interface, Co-lay PCI-Ex4) - 1* M.2 M-key (2242/2280 SATA interface, Co-lay SATA4)
Expansion	<ul style="list-style-type: none"> - 1* M.2 B-key (3042/3052, USB3.0/USB2.0, Support 4G/5G Module) - 1* M.2 E-key (2230, CNVi/PCI-Ex1/USB2.0, Support WIFI/BT Module) - 1* PCIe 4.0 x16 slot - 1* PCIe 3.0 x4 slot - 2* PCI slots
Ethernet	<ul style="list-style-type: none"> - 2* Intel® i225-V 100/1000/2500Mbps - 1* Intel® i219-V 10/100/1000Mbps
Graphics	<ul style="list-style-type: none"> - Intel® UHD Graphics, shared memory - 1* HDMI2.0 (Max Resolution: 4096x2304@60Hz) - 1* DP1.4 (Max Resolution: 7680x4320@60Hz) - 1* VGA (Max Resolution: 2560x1600@60Hz) - Support Triple Displays
Audio	<ul style="list-style-type: none"> - HD audio: Realtek ALC888S
Watchdog Timer	<ul style="list-style-type: none"> - From Super I/O to drag RESETCON# - 256 segments (10sec ~ 255min)
Internal I/O	<ul style="list-style-type: none"> - 4* USB2.0 (PH2.54) - 1* USB2.0 (Vertical) - LM26-H610: 8* RS232 - LM26-H610-6C: 4* RS232 - 16bit GPIO (5V) - 4* SATAIII (SATA4 Co-lay M-key-M2) - 1* 24+8pin Power connector - 1* SIM Card hold - 1* Chassis intrusion - 1* FP_ Audio - 1* PS/2 + 1* SMBUS + 1*AT model - 1*CPU FAN Header(Smart FAN) + 2*SYSTEM FAN Header
External I/O	<ul style="list-style-type: none"> - 3* USB3.2(Gen.1) - 3* USB2.0 - 1* VGA - 1* HDMI2.0 - 1* DP1.4 - 2* COM (RS232/422/485) - 3* RJ45 - 1* 3Jack (Line-in + Line-out + MIC)
Power	<ul style="list-style-type: none"> ATX PWR (24+8pin), AT/ATX Supported - AT: Directly PWR on as Power input ready - ATX: Press Button to PWR on after Power input ready
Compliance	<ul style="list-style-type: none"> - CE, FCC, LVD, RoHS, REACH (Option)
Temperature	<ul style="list-style-type: none"> - Operating Temperature: -10 ~ 60° C - Storage Temperature: -20 ~ 70° C - Humidity: 10% ~ 90% RH @40°C (non-condensing)
OS Support	<ul style="list-style-type: none"> - Windows 10 / 11, Linux