



999.00 EUR  
 incl. 19% VAT, plus [shipping](#)

- For Celeron M 1.5Ghz
- FANLESS carpc system
- Integr. Autostart Controller
- Dualchannel VGA

CARTFT.COM



Support: [Assembling Tutorial \[DE\]](#) | [Assembling Tutorial \[EN\]](#) | [Dual-Out-HowTo \[EN\]](#)

Fanless CarPC-barebone for use with Intel P4/Celeron M CPU.  
 Celeron-M 1.7Ghz is recommended for fanless operation.

The CALU-M(2)C-Series has an integrated car-power supply (direct connectable to car battery and ignition plus + integrated automatic Start/Stop-Controller).

The time intervals for automatic Start and Stop can be adjusted in the BIOS of the PC !

CALU specifications	
Processor (supported)	Intel Pentium M processor or Celeron M processor (Dothan or Banias) 1.3GHz or higher
Memory	Supports DDR 333/266 DIMM RAM 0.8" low profile 2x memory slots ! Maximum : 2 GB
Video	Intel Extreme Graphics 2 Supports up to 64MB DVMT video memory
Audio	Software AC '97 Audio CODEC

<b>Peripheral Connection</b>	<p>Front :</p> <ul style="list-style-type: none"> <li>1 x IEEE 1394 Firewire port</li> <li>1 x USB 2.0 / 1.1 Port</li> <li>1 x MIC Port</li> <li>1 x Ear Phone output Jack</li> <li>Power-on button</li> <li>Reset button</li> <li>Power-on and HDD LED</li> </ul> <p>Rear :</p> <ul style="list-style-type: none"> <li>1 x RS232 COM port</li> <li>1 x RJ45 10/100Mb Fast Ethernet</li> <li>1 x Line-Out output Jack</li> <li>2 x USB 2.0 / 1.1 Ports</li> <li>1 x 15 pin VGA</li> <li>1 x DVI</li> </ul>
<b>Storage</b>	<p>One 2.5 inch Hard Disk and 9.5mm high. (Support Ultra DMA 33/66/100).</p>
<b>Weight &amp; Size</b>	<p>System approximately 3kg (fully equipped). System Dimension: 155 x 255 x 55 mm</p>
<b>Power req.</b>	<p>9-16VDC, 5A</p>

**Accessory**

<b>Storage</b>	<p>Supports all Standard Slim CD-ROM/DVD-ROM, CD-RW, DVD-RW Combo Supports all 2.5" standard IDE hard drive, ATA-100/66/33.</p>
<b>Scope of supply</b>	<p>Connector cable for Plus, ignition plus and ground Barebone Barebone CPU Kühlkörper</p>

Installation Tutorial : [Support / Manuals](#)

Graphics driver for 800x480 resolution : [Here](#)