

**0.00 EUR**

incl. 19% VAT, plus shipping

- **STM32L072 Controller !**
- **IP67 Rated Enclosure !**
- **Wall mount / Pole Mount !**
- **1 × RS-485 interface !**

The EC-M12-BC-C6-C-B is a rugged, IP67-rated IoT telemetry unit designed for reliable outdoor and remote monitoring applications. Powered by high-capacity non-rechargeable lithium batteries, it delivers years of autonomous operation even in harsh environments.

Built on the ultra-low-power STM32L072CZT6 MCU, the device supports multi-network cellular connectivity for seamless data transmission. It also integrates directly with industrial RS-485 interfaces, making it ideal for use in utilities, environmental monitoring, agriculture, and industrial asset management.

- EC-M12-BC-C6-C-B
- IP67 Rugged Industrial Design
- 38000 mAh Long Battery Life
- STM32L072 Reliable Operation
- SIM7070 Secure Connectivity
- Serial interface configuration for third-party industrial sensors and field instruments.
- 12V sensor excitation

Range of product

Product type

Rated supply voltage

Model B

NORVI SENSOR NODE

Built-in Battery LiSoCL

Communication	SIMCOM SIM7070 – 2G / NB-IoT
Sensor Power	12V DC / 5V DC
Displays and Visual Indicators	Connectivity Indicator
Enclosure	ABS + PolyCarbonate / IP67
Mounting / Installation Method	Wall mount / Pole Mount
Terminal Type	M8 – 8 pin connector
Dimensions	146 x 50 x 90 mm
IP degree of protection	IP67
Operating altitude	0...2000m
Operating temperature	-40 to +85 °C
Shock resistance	Not Applicable
Resistance to electrostatic discharge	VBAT/GND: ± 5 kV / ± 10 kV Antenna: ± 5 kV / ± 10 kV USB: ± 4 kV / ± 8 kV UART: ± 4 kV / ± 6 kV Other pads: ± 1 kV / ± 2 kV
Certifications	EN 61131-2:2007 EN 61010-1:2010+A1:2019 EN IEC 61010-2-201:2018 2014/30/EU- Electromagnetic Compatibility (EMC) Annex III, Part B, Module C
Product Unified Code / Part Number	EC-M12-BC-C6-C-B

Peripherals

Card Type	MicroSD
Interface	SPI
Modem	SIM7070
Technology	LTE Cat-M1 NB-IoT (NB1/NB2) GSM/GPRS fallback (2G)
Coverage / Supported Bands	(B1/B2/B3/B4/B5/B8/B12/B13/B18/B19/B20/B26/B27/B28/B66) for Cat-M/NB, plus quad-band GSM (850/900/1800/1900 MHz).
Data Rate	LTE Cat-M1: up to 588 kbps DL / 1119 kbps UL NB-IoT: up to 26 kbps DL / 62.5 kbps UL GPRS: 85.6 kbps DL / UL