

Front





0.00 EUR

incl. 19% VAT, plus shipping

- **Intel LGA1851 !**
- **Intel Q870 !**
- **2 x 2.5GbE !**
- **4 Display support !**

Rear



- Supports Intel® LGA1851 Socket Processors of the Arrow Lake-S series with up to 65W TDP
- High-Performance Memory: 2 x DDR5 CSO-DIMM in dual-channel mode, up to 96GB
- High-Speed Networking: 2 x 2.5GbE for fast and reliable connectivity
- Supports up to four 4K displays via 2 x HDMI®, 1 x DP and 1 x Type-C DP
- Flexible Storage & Expansion: 2 x SATA, 2 x M.2 M-Key, 1 x M.2 E-Key, 1 x M.2 B-Key and 1 x PCIe x16
- Wide Range Power Input: DC-in 12~36V for industrial applications

SYSTEM

MB FORM FACTOR

CPU

CHIPSET

MEMORY

BIOS

WAKE ON LAN

Rackmount

Intel® LGA1851 Socket, Processor Arrow Lake-S
(MAX. TDP 65W)

Intel® Q870

2 x DDR5 6400MT/s, Dual Channel CSO-DIMM,
up to 96GB

UEFI

Yes

WATCHDOG TIMER	255 Levels
SECURITY	Intel® PTT (fTPM)
RTC BATTERY	Lithium Battery
OS SUPPORT	Windows® 11 (64bit) Linux
POWER	
POWER REQUIREMENT	DC-in 12~36V
POWER ON MODE	AT / ATX (Default) Mode
DISPLAY	
GPU	Intel® Graphics
Type-C DP	1 x Type-C DP1.4a (Max Resolution: 4096 x 2160@60Hz)
DP	1 x DP1.4a (Max Resolution: 4096 x 2160@60Hz)
HDMI®	2 x HDMI® 2.1 TMDS (Max Resolution: 4096 x 2160@60Hz)
MULTIPLE DISPLAY	Support 4 Displays
AUDIO	
CODEC	Realtek codec
AMPLIFIER	3W
LAN	
ETHERNET	1 x RJ45 for Intel® I226-V 2.5GbE 1 x RJ45 for Intel® I226-LM 2.5GbE
SYSTEM I/O	
REAR PANEL I/O	2 x RJ45 4 x USB3.2 (Gen 2) 2 x USB 2.0 1 x USB 3.2 Gen 2 Type-C support DP1.4a display output 2 x HDMI® 1 x DP 1 x Audio (Line out, MIC Combo) 1 x DC-in (Lockable) 2 x RS-232 2 x RS-232/422/485
FRONT PANEL I/O	1 x Power Button 1 x Reset Button 1 x Power LED 1 x HDD LED 2 x USB 2.0
STORAGE	
SATA	2 x 2.5" SATA 6Gb/s internal drive bay (only Support 2.5" HDD with a hight ? 10mm)
RAID	Intel® VMD RAID 0, 1 or SATA RAID 0, 1, 5
EXPANSION	
PCIe	1 x PCIe x16

M.2	1 x M-Key 2242 (PCIe Gen 4 x4) support NVMe 1 x M-Key 2280 (PCIe Gen 4x4 w/ SATA interface) support NVMe 1 x E-Key 2230 (USB 2.0/PCIe Gen 4 x1) Support CNVio 1 x B-Key 3042/3052 (PCIe Gen 4x1/USB3.2/USB 2.0) Support 4G/5G Module 1 x Nano SIM Card Slot
SIM	
MECHANICAL	
DIMENSIONS (W x H x D)	430.0 (W) x 252.0 (D) x 44.0 (H) mm
GROSS WEIGHT	4.2kg
NET WEIGHT	5.2kg
CONSTRUCTION	Metal Heatsink + Metal Chassis
ENVIRONMENT & CERTIFICATION	
SHOCK	15G, 11ms duration
DROP	ISTA PROJECT 1A
VIBRATION	1 Grms/ 5~ 500Hz/ Operation
OPERATING TEMPERATURE	0°C ~ 50°C (32°F ~ 122°F)
STORAGE TEMPERATURE	-40°C ~ 85°C (-40°F ~ 185°F)
OPERATING HUMIDITY	10 ~ 90% Relative Humidity, Non-condensing
STORAGE HUMIDITY	10 ~ 90% @40°C, Non-condensing