114.95 EUR
incl. 19% VAT, plus shipping

- **8-Port Gigabit !**
- **Unmanaged Switch !**
- **16 Gbps Switching !**
- **AT-GS910/8-50 !**

The Allied Telesis AT-GS910/8-50 is an unmanaged Gigabit Ethernet switch for desktop and small network environments. It provides eight 10/100/1000T RJ-45 ports and enables simple network expansion with minimal setup requirements.

The switch supports auto-negotiation, auto MDI/MDI-X and half- or full-duplex operation. Features including BPDU and EAP pass-through, flow control, loop guard, jumbo frames and Energy-Efficient Ethernet support reliable and energy-efficient network operation.

**Key Features:**

- 8x 10/100/1000T Gigabit Ethernet RJ-45 ports
- Unmanaged switch for desktop and small networks
- 16 Gbps switching capacity and 11.9 Mpps throughput
- Auto-negotiation and auto MDI/MDI-X
- Supports BPDU/EAP pass-through, flow control and loop guard
- Supports jumbo frames up to 9216 bytes
- Internal power supply, 100 - 240V AC

| | |
|---|---|
| **Network Interfaces** | 8x 10/100/1000T RJ-45 |
| **Network Media** | 10 Mbps: Two-pair Category 3 or better unshielded twisted pair cable, maximum 100 m<br>100 Mbps: Two-pair Category 5 unshielded twisted pair cable, maximum 100 m<br>1000 Mbps: Four-pair Category 5e unshielded twisted pair cable, maximum 100 m |
| **Standards and compliance** | IEEE 802.3 10BASE-T<br>IEEE 802.3u 100BASE-TX<br>IEEE 802.3ab 1000BASE-T<br>IEEE 802.3x Flow Control<br>IEEE 802.3az Energy-Efficient Ethernet |
| **Switching Capacity** | 16Gbps |

| | |
|---|---|
| **Throughput** | 11.9Mpps |
| **MAC Address Table** | Max 4K |
| **Packet Buffer** | 128Kbytes |
| **Jumbo Frames** | 9216bytes |
| **Power supply requirements** | 100 - 240V AC<br>50 - 60Hz<br>0.2A |
| **Dimensions (W x D x H)** | 210 x 121 x 38 mm |
| **Operating Temperature** | 0-50C (32-122F) |
| **Features** | BPDU/EAP pass-through<br>Flow control<br>Loop guard<br>Jumbo Frame<br>Eco-friendly<br>Half/full-duplex<br>Auto-negotiation<br>MDI/MDI-X |
| **Certification** | UL60950-1, 2nd Edition<br>CSA C22.2 No.60950-1-07, 2nd Edition<br>IEC60950-1(UL-EU, UL-CB)<br>EAC certification<br>EN55024<br>ICES Class A<br>VCCI Class A<br>FCC Class A<br>RCM<br>CE<br>EN55022<br>CISPR 55022<br>EU RoHS compliant |
| **Mounting** | Wall-mount or desktop<br>No bracket |