



999.00 EUR

incl. 19% VAT, plus shipping

- Mini-PCI Express
- 2x SO-DDR2
- Dual LAN
- ATI Direct X9!

Bundle: Mainboard is shipped together with AMD Sempron 2100+ 1Ghz CPU (8W) and passive cooling heatsink.

D2703-S is a special designed mainboard for industrial applications. Extended temperature ranges, long life capacitors and a special tin-plated PCB built an optimal hardware basis for industrial systems. Additionally we offer an extended availability (up to 48 months) and additional hardware and software documentation. D2703-S provides dual GBE LAN Ethernet, Controller on board, Serial ATA II RAID, Audio on board (HDA), ATI Radeon Graphics, CF support for Embedded OS, USB 2.0, Instantly Available PC (IA-PC) and Improved Thermal Management/System Monitoring.

Board Size Mini-ITX: 6.7" x 6.7" (170 x 170 mm) Chipset AMD M690E & SB600 2 SO DIMM Sockets (1.8V), 256MB - 8GB, Single Channel or Dual Memory Channel DDR2 800/667 SDRAM, unbuffered, no ECC AMD Mobile Turion™ 64 X2 Dual Core Processors AMD Mobile Sempron™ Processors Processors Mobile Socket S1g1 (PGA 638), max. 35W, HyperTransport[™] 1; 800MHz BTX12V (24 Pin) or ATX12V (20 Pin) Power Supply required Support for Soft-Off Power Supplies or 24V / 5A via DC-connector (Rear I/O connector or onboard connector) Power Specification 5V and 3.3V Supply Voltage on PCI Slots (PCI Rev. 2.3) 3.3V Auxiliary Supply Voltage on PCI Slots (Wake-Up Function)

3.3V Auxiliary Supply Voltage on PCI Slots (Wake-Up Function)
On board CPU Voltage Regulator, 5V / 2A Auxiliary Power
(BTX/ATX only)
required for USP Wake Up from Save to PAM. Save to Disk

required for USB Wake-Up from Save-to-RAM, Save-to-Disk Integrated ATI Radeon X1250 graphics; shared memory (up to 256MB);

DirectX 9 compliant; DVI, VGA and Dual Channel LVDS support Realtek ALC262 (HD Audio);

HW 3D Stereo Enhancement; SW Wavetable Synthesis Support Dual Realtek RTL8111C 10/100/1000 Ethernet controller

1x ATA 133 Interface for 1 Drive

4x Serial ATA II 300 Interfaces (max 3 GBit/s); up to 4 Drives; RAID 0/1/10

1x CF Interface (Typ I)

Graphics

Audio

LAN

Drives



BIOS

Special Features

Scope of supply:

- Fujitsu D2703-S Mainboard
- Fujitsu CPU-heatsink/fan
- 1x SATA cable
- 1x IDE cable



Phoenix TrustedCore BIOS Version V6.00

modified and adapted by Fujitsu Siemens Computers;

Recovery BIOS, SM-BIOS (DMI),

BIOS Update via USB (stable user settings), Quick Boot, Logo

Boot

Quiet Boot, Plug & Play, Automatic DRAM and PCI Configuration,

BIOS Support for S.M.A.R.T., Advanced Power Management,

ACPI S3 (Save-to-RAM), ACPI S4 (Save-to-Disk),

Wake on time from S5; Flexible LVDS Support

Silent Fan: Independent temperature related processor fan and

system fan supervision and control

System Guard : View and adjust Silent Fan Silent Drives Noise

reduction for optical and hard disk drives

Recovery BIOS: Restores a corrupted BIOS Desk Update Simple

driver update with Driver&Utilities DVD

Multi Boot : Comfortable boot from any boot device