RUGGED TABLET PC (Model NO. : CTFPND-8)

Waterproof /Dustproof/Dropproof/Full function/Hi-Rel/Low-Power/Extensible




Introduction

CTFPND-8 tablet pc is with the current 7-inch tablet three anti-industrial-grade IP67 rated in the highest standard of protection, the use of aluminum alloy internal frame with 1.2mm tempered glass touch screen, you can spot the wild through a rigorous three anti-testing, internal frame it is able to withstand four feet (1.2 m) drop at any angle, waterproof, dustproof, drop, scratch, is expected to reach MIL-STD-810G military standards. In addition, to facilitate the expansion of enterprise customers, products, internal circuitry also set aside a standard data interface, you can easily Beidou navigation, RFID, barcode scanning, fingerprint recognition, second generation ID card identification, nfc, identification card and other related enterprise application module expansion.

Hardware

CPU: 1. G Hz x Cortex A core RAM/ROM TWO-IN-ONE :1G+4G EMCP 7 7inch **IPS/AFFS** 1024x600 Display : luminance :400CD/M² Sunlight Readable Touch Panel : Capacity multi-touch panel 5 points touch capacity screen / toughened glass TP Basic Function : 2G/3G/BT/GPS/WIFI/FM/ Axis Accelerometer Sensor/Orientation Sensor Gravity Sensor/Linear Acceleration Sensor Rotation Vector Sensor/Magnetic Field Sensor/Gyroscope Sensor Extensible Function : Fingerprint Reading/ RFID/ Beidou Navigation/high precision sub-meter GPS/2nd-Generation ID Card Reading / Ziggbee.

Dimension



(nnn)		$(\Pi \Pi \Pi)$
	1	

Specification			
The progress of products	МР		
CarTFT.com Model No.	CTFPND-8		
СРИ	MTK6589 1.2G Hz x4 Cortex A7 Quad Core		
GPU	Power VR SGX544 MP2		
RAM/ROM TWO IN ONE	1G LPDDR2 /4G EMCP		
Storage(Optional)	8GB-64GB(CLASS10 TF inside)		
Display	7inch IPS/AFFS 1024x600 luminance :400CD/M ² Sunlight Readable		
Touch Panel	Capacity multi-touch panel 5 points touch capacity screen / toughened glass		
Touch ranei	TP		
3G	WCDMA/GSM/HSPDA 14.4m		
call	YES		
Band 2G STANDARD	2G:850/900/1800/1900		
Band 3G STANDARD	3G:Band1、Band5		
Band 3G (custom)	3G:Band2、Band5		
Band 3G (custom)	3G:Band2、Band8		
WIFI (Wifi Direct)	802. 11B/G/N		

MESSAGES		YES	
MMS		YES	
Bluetooth		YES 4.0	
GPS		YES	
Axis Accelerometer Sensor		YES	
Orientation Sensor		YES	
Gravity Sensor		YES	
Linear Acceleration Sensor		YES	
Rotation Vector Sensor		YES	
Magnetic Field Sensor		Optional	
Gyroscope Sensor		Optional	
Beidou navigation		Optional	
Wireless charging		Optional	
RFID		Optional	
AGPS		YES	
FM RADIO		YES	
Front Camera		2. OM	
Back Camera		8.0M (AF) [5.0M before April 2015]	
Battery		10000MAh	
Speaker		Built-in single loud speaker	
Headphone		3.5mm stereo jack	
MIC		Internal MIC-phone	
SD / MMC		TF slot, capacity up to 32GB	
SIM-Card		Yes	
Car Charger		5V, 2A,Mico USB	
Video Performance		Video Decoding Format: H.264, MPEG4, H.263 Support File Format: RM, RMVB, AVI, MPEG4, F1V, 1080P	
Operating Syst	em	Android OS 4.2	
Serial port		RS232/TTL 3.3V X1/GPIO 3.3V X1/200ma VBT X2	
Internal space		32mmx32mmx5mm X2	
Environmental test	Shake-proof	1-19Hz/1.0mm ;19-200Hz/1.0g	
	Drop-proof	MIL-STD-810G/Method516.6/Procedure IV	
	Water-proof	Class 6	
	Dustp-roof	Class 6	
	Soundness	MTBF>50000h; MTTR<0.5h	
		Operating ambient temperature: (-20° to 60° C)	
		Nonoperating temperature: (-40° to 80° C)	
		Relative humidity: 5% to 95% noncondensing	
		Maximum operating altitude: 15,000 feet (4500 m)	