THE POSSIBILITIES ARE INFINITE



DATA SHEET

Preliminary

IPC Mini-ITX Chassis

version!

Oct 2009 Issue **Product** Chassis

Suitable for Industrial Mainboard D2963-Sx

Pages

IPC Mini-ITX Chassis suitable for D2963-Sx

Features

Front: Illuminated Power Button Inside: Mounting options for:

- Mini-ITX Mainboard D2963-Sx
- PCI-Riser Card for low profile PCI cards
- **USB WLAN Module**
- 2,5" HDD

Intrusion switch for case opening detection

System fan (4-pin PWM)

Apertures suitable for I/O of D2963-S Rear:

- 2x PS/2 (keyboard and mouse)
- 2x LAN
- COM₁
- DVI-I
- DC in
- 4x USB Additional apertures for:

- aperture for 2nd serial port
- aperture for opt. USB WLAN
- 1 slot for low profile PCI cards
- aperture for Kensington lock

Operating conditions

Temperature range Humidity

0°C - 50°C depending on config. 10% - 90% relative humidity

(non-condensing)

Physical specifications

Dimensions 250 x 52 x 191 mm

Approvals CE, further approvals tbd.

Optional Parts

- Mini-ITX Mainboard D2963-S1or D2963-S2
- **VESA Mounting Kit**
- USB WLAN Module incl. cover
- 2nd serial port cable
- PCI Riser Card
- 19V AC Adapter with EU or UK power cord
- 24V AC Adapter with EU or UK power cord





Power Book IPC with VESA Mounting Kit directly attached to Monitor

Information about environmental care, policies, programs and our Environmental Guideline FSC 03230: ts.fujitsu.com /aboutus

Take back and Recycling information: ts.fujitsu.com/recycling